



[Read More](#)

**SKU:**

**Price:**

**Stock:** instock

**Categories:** [Uncategorized](#)

## Product Description

**Specification :-** Type : Electronic lift Temperature range : Ambient to 220°C Heating power : 1500W. Operating voltage : 220 – 240 V at 50/60 HZ Display : LCD display Temperature deviation : at 2°C. Rotation speed : adjustment 20 to 280 RPM. **Features :-** - Cordless power supply allows emptying and refilling of water bath without unplugging. - LCD display indicates set and actual values of heating bath temperature, rotation speed, and lift height adjustment. - Auto lift from heating bath at the time of power failure - Accommodate flask size from 50 ml to 5000 ml. - Multifunction comb clip - A plastic coating on glass (P+G) - Condensate trap to trap external moisture formed on condenser - Provided with flask of 1000 ml each flask with flask joint SJ29/32 - Evaporation flask feeding via stopcock. - Rust free body material - Infrared bi-directional communication between heating bath and rotary evaporator **Vacuum Pump :** Operating voltage : 220 – 240 V at 50/60 HZ Membrane Pump : Two stage PTFE with window heads Flow rate : 1.8 m<sup>3</sup>/hr. Vacuum : 5 mbar **Vacuum Controller :** Display : Touch screen Operating mode : Manual, Timer, Continuous, Drying etc. **Features :-** - Rotary knob / button Allows in both ways - Built in solvent library (extended version: 60 Solvents). - Allows to add and

# AGN ENTERPRISES

MANUFACTURER & SUPPLIER  
ALL KINDS OF LABORATORY EQUIPMENTS



continuously **Accessories** :- - Cord & plug - warranty Card - Instruction Manual